

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : APESIN HANDACTIVE F
UFI : DNX8-50VA-D00D-ADXF

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Biocidal product
Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : Tana Chemie GmbH
Rheinallee 96
55120 Mainz
Telephone : +49613196403
Telefax : +4961319642526
E-mail address : Produktsicherheit@werner-mertz.com
Responsible/issuing person
Contact person : Product development / product safety

1.4 Emergency telephone

EU: 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.
Serious eye damage, Category 1 H318: Causes serious eye damage.
Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

Supplemental Hazard Statements	:	EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary Statements	:	Prevention: P210 P233 P261 P271 Response: P304 + P340 P305 + P351 + P338 + P310 Storage: P403 + P235 P405 Disposal: P501	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Avoid breathing vapors. Use only outdoors or in a well-ventilated area. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of container into the collection of recyclables only when it is completely empty.

Hazardous ingredients which must be listed on the label:

propan-2-ol
propan-1-ol

Safety data sheet available on request.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
propan-2-ol	67-63-0	Flam. Liq. 2; H225	>= 30 - < 50

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

	200-661-7 603-117-00-0 01-2119457558-25	Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	
propan-1-ol	71-23-8 200-746-9 603-003-00-0 01-2119486761-29	Flam. Liq. 2; H225 Eye Dam. 1; H318 STOT SE 3; H336	>= 30 - < 50

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Call a POISON CENTER or doctor/ physician.
- Move to fresh air.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.
Take off contaminated clothing and shoes immediately.
Wash clothing before reuse.
Call a POISON CENTER or doctor/ physician.
- Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
Protect unharmed eye.
If easy to do, remove contact lens, if worn.
Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Continue rinsing eyes during transport to hospital.
- Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
Protect unharmed eye.
Continue rinsing eyes during transport to hospital.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Do NOT induce vomiting.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Obtain medical attention.

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : corrosive effects

Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : For specialist advice physicians should contact the Poisons Information Service.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Water spray jet
Dry powder

Alcohol-resistant foam

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapors accumulating to form explosive concentrations.
Vapors can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Use mechanical handling equipment.
- Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations"., For disposal considerations see section 13., Refer to section 15 for specific national regulation.
For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations"., Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapors or spray mist.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Container may be opened only under exhaust ventilation hood.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
- Advice on protection against fire and explosion : Use explosion-proof equipment. Avoid formation of aerosol. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards. Store at room temperature in the original container.
- Store in original container. Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards. Store at room temperature in the original container.

- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : Biocidal product

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
propan-2-ol, propan-2-ol (Manufacturing), propan-2-ol (Manufacture-strong acid process)	Workers	Skin contact	Long-term systemic effects	888 mg/kg
	Workers	Inhalation	Long-term systemic effects	500 mg/m3
	Consumers	Skin contact	Long-term systemic effects	319 mg/kg
	Consumers	Ingestion	Long-term systemic effects	26 mg/kg
	Consumers	Inhalation	Long-term systemic effects	89 mg/m3
propan-1-ol	Workers	Skin contact	Long-term systemic effects	136 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	81 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	1723 mg/m3
	Workers	Inhalation	Long-term systemic effects	268 mg/m3
	Consumers	Ingestion	Long-term systemic effects	61 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	1036 mg/m3
	Consumers	Inhalation	Long-term systemic effects	80 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
propan-2-ol, propan-2-ol (Manufacturing), propan-2-ol	Fresh water	140,9 mg/l

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

(Manufacture-strong acid process)		
	Sea water	140,9 mg/l
	Fresh water sediment	552 mg/kg
	Sea sediment	552 mg/kg
	Soil	28 mg/kg
	intermittent release	140,9 mg/l
	STP	2251 mg/l
	Oral	160 mg/kg
propan-1-ol	Fresh water	10 mg/l
	Sea water	1 mg/l
	intermittent release	10 mg/l
	STP	96 mg/l
	Sea sediment	2,28 mg/kg
	Fresh water sediment	22,8 mg/kg
	Soil	2,2 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : not required under normal use

If splashes are likely to occur, wear:

Tightly fitting safety goggles

If splashes are likely to occur, wear:

Tightly fitting safety goggles

Hand protection

Material : not required under normal use

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

Material : For prolonged or repeated contact use protective gloves.

It is suggested the usage of chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.

As alternative, a different type of gloves might be used if, accordingly to the recommendations of the producer, guarantee the same level of protection.

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Skin and body protection : not required under normal use

Respiratory protection : Not required; except in case of aerosol formation.

Recommended Filter type:

ABEK-P3-filter

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : colorless

Odor : alcohol-like

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Flammability (liquids) : No data available

Lower explosion limit : No data available

Upper explosion limit : No data available

Flash point : 23 °C

Ignition temperature : No data available

Decomposition temperature : No data available

pH : ca. 5,4, 1 %
at 20 °C

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Vapor pressure	: No data available
Density	: ca. 0,852 g/cm ³ at 20 °C
Relative density	: No data available
Relative vapor density	: No data available
Particle characteristics	: No data available

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.
No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
No decomposition if used as directed.
Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Our company is strongly against animal testing.
Our company does not place any orders for animal testing for the finished product or the ingredients.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

However, as a result of EU legislation (REACH Regulation), the manufacturers of ingredients or EU importers are obliged to test ingredients with regard to their effects on human health and the environment before they are brought onto the market. Some of the tests made necessary by this took place decades ago.

Acute toxicity

Acute toxicity : Not Rated

Components:

propan-2-ol

67-63-0:

Acute oral toxicity : LD50 Oral (Rat): 5.840 mg/kg
Method: OECD Test Guideline 401

LD50 Oral (Rat): 4.570 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 47,5 mg/l
Exposure time: 8 h
Method: OECD Test Guideline 403

LC50 (Rat): 72,6 mg/l
Exposure time: 4 h

LC50 (Mouse): 27,2 mg/l
Exposure time: 4 h

LC50 (Rat): 25 mg/l
Exposure time: 6 h
Method: OECD Test Guideline 403

LC50 (Rat): 30 mg/l
Exposure time: 4 h

LC50 (Rat): 10000 ppm
Exposure time: 6 h

Acute dermal toxicity : LD50 (Rabbit): 12.800 mg/kg
Method: OECD Test Guideline 402

LD50 Dermal (Rabbit): 12.870 mg/kg
Method: OECD Test Guideline 402

LD50 Dermal (Rabbit): 13.900 mg/kg
Method: OECD Test Guideline 402

LD50 Dermal (Rabbit): 13.400 mg/kg

propan-1-ol

71-23-8:

Acute oral toxicity : LD50 (Rat): ca. 8.000 mg/kg

LD50 (Rat, male): 5.400 mg/kg

Acute inhalation toxicity : LC50 (Rat): 33,8 mg/l
Exposure time: 4 h

LC50 (Rat): 39,1 mg/l

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

Exposure time: 1 h

Acute dermal toxicity : LD50 (Rabbit): 4.032 mg/kg

Skin corrosion/irritation

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

propan-2-ol

67-63-0:

Species : Rabbit
Result : No skin irritation

propan-1-ol

71-23-8:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Product:

Remarks : May cause irreversible eye damage.

Components:

propan-2-ol

67-63-0:

Species : Rabbit
Result : irritating

Respiratory or skin sensitization

Product:

Remarks : No data available

Components:

propan-2-ol

67-63-0:

Test Type : Buehler Test
Species : Guinea pig
Result : Does not cause skin sensitization.

Germ cell mutagenicity

Germ cell mutagenicity : Not Rated

Components:

propan-2-ol

67-63-0:

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

propan-1-ol

71-23-8:

Genotoxicity in vitro : Test Type: Ames test
Result: negative

Carcinogenicity : Not Rated

Reproductive toxicity : Not Rated

STOT-single exposure : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT-repeated exposure : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration toxicity : Not Rated

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

propan-2-ol, propan-2-ol (Manufacturing), propan-2-ol (Manufacture-strong acid process)

67-63-0:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1.400 mg/l
Exposure time: 96 h

LC50 (Pimephales promelas (fathead minnow)): 9.640 mg/l
Exposure time: 96 h

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

		LC50 (Leuciscus idus (Golden orfe)): > 100 mg/l Exposure time: 48 h Test Type: static test GLP: no
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 13.299 mg/l Exposure time: 48 h EC50 (Daphnia magna (Water flea)): 9.714 mg/l Exposure time: 24 h EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test GLP: no (Daphnia): > 10.000 mg/l Method: OECD Test Guideline 202 NOEC (Daphnia magna (Water flea)): 30 mg/l Exposure time: 21 d EC50 (Daphnia magna (Water flea)): 10.000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	IC50 (Desmodesmus subspicatus (green algae)): > 1.000 mg/l Exposure time: 72 h Test Type: Growth inhibition EC50 (Pseudokirchneriella subcapitata (microalgae)): > 100 mg/l Exposure time: 72 h Test Type: static test GLP: no ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l Exposure time: 72 h EC50 (Scenedesmus subspicatus): > 100 mg/l Exposure time: 72 h Test Type: static test
Toxicity to microorganisms	:	EC50 (Aliivibrio fischeri): 17.700 mg/l Exposure time: 5 min EC10 (Pseudomonas putida): 5.175 mg/l Exposure time: 18 h Method: DIN 38412
propan-1-ol		
71-23-8:		
Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 4.555 mg/l Exposure time: 96 h (Pimephales promelas (fathead minnow)): 4.480 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 3.644 mg/l Exposure time: 48 h Method: Directive 67/548/EEC, Annex V, C.2.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

		EC50 (Daphnia magna (Water flea)): 3.640 - 8.150 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 9.170 mg/l Exposure time: 48 h Test Type: static test NOEC (Chlorella pyrenoidosa): 1.150 mg/l Exposure time: 48 h Test Type: static test EC0 (Scenedesmus quadricauda (Green algae)): 3.100 mg/l
Toxicity to microorganisms	:	EC50 (Photobacterium phosphoreum): 17,7 g/l Exposure time: 5 min EC0 (Pseudomonas putida): 2.700 mg/l Exposure time: 16 h IC50 (Bacteria): > 10.000 mg/l Exposure time: 16 h EC0 (see user defined free text): 3.100 mg/l EC50 (activated sludge): > 1.000 mg/l Exposure time: 3 h

12.2 Persistence and degradability

Components:

propan-2-ol, propan-2-ol (Manufacturing), propan-2-ol (Manufacture-strong acid process)

67-63-0:

Biodegradability	:	Result: rapidly biodegradable Biodegradation: 95 % Exposure time: 21 d Method: OECD 301 E Inoculum: activated sludge Result: rapidly biodegradable Biodegradation: 53 % Exposure time: 5 d Result: rapidly biodegradable Biodegradation: > 70 % Exposure time: 10 d GLP: no Biodegradation: 99,9 % Method: see user defined free text
------------------	---	--

Chemical Oxygen Demand (COD) : 2,32 g/kg

ThOD : 2,40 g/g

propan-1-ol

71-23-8:

Biodegradability : Result: Readily biodegradable.

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

Biodegradation: 75 %
Exposure time: 20 d
Method: Closed Bottle test

Result: rapidly biodegradable
Biodegradation: 83 %
Exposure time: 5 d
Method: OECD 301 D

Result: rapidly biodegradable
Biodegradation: 83 - 92 %
Exposure time: 28 d
Method: OECD 301 F

Chemical Oxygen Demand (COD) : 2,23 g/g

ThOD : 2,4 g/g

12.3 Bioaccumulative potential

Components:

propan-2-ol, propan-2-ol (Manufacturing), propan-2-ol (Manufacture-strong acid process)

67-63-0:

Bioaccumulation : Bioconcentration factor (BCF): 3

Remarks: No bioaccumulation is to be expected (log Pow <= 4).

Partition coefficient: n-octanol/water : log Pow: 0,05

propan-1-ol

71-23-8:

Bioaccumulation : Bioconcentration factor (BCF): 3

12.4 Mobility in soil

Components:

propan-2-ol, propan-2-ol (Manufacturing), propan-2-ol (Manufacture-strong acid process)

67-63-0:

Distribution among environmental compartments : Koc: 25
Remarks: Highly mobile in soils

propan-1-ol

71-23-8:

Distribution among environmental compartments : Koc: 33
Remarks: Highly mobile in soils

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

Components:

propan-2-ol, propan-2-ol (Manufacturing), propan-2-ol (Manufacture-strong acid process)

67-63-0:

Assessment : Not very persistent and very bioaccumulative (vPvB).. Not persistent, bioaccumulative, and toxic (PBT).

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

Waste Code : European Waste Catalog
20 01 29*
According to the European Waste Catalog, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : 1987
IMDG : 1987
IATA : 1987

14.2 UN proper shipping name

ADR : ALCOHOLS, N.O.S.
(ISOPROPANOL)

IMDG : ALCOHOLS, N.O.S.
(ISOPROPANOL)

IATA : ALCOHOLS, N.O.S.

14.3 Transport hazard class(es)

ADR : 3
IMDG : 3
IATA : 3

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

14.4 Packing group

ADR

Classification Code : F1
Packaging group : III
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

IMDG

Packaging group : III
Labels : 3
EmS Number : F-E, S-D

IATA

(Cargo) : ALCOHOLS, N.O.S., Alcohols, n.o.s.
Packaging group : III
Labels : 3

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

For personal protection see section 8.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P5c	FLAMMABLE LIQUIDS	5.000 000067	50.000 000067

TA Luft List (Germany) : Total dust: Not applicable
: Inorganic substances in powdered form: Not applicable
: Inorganic substances in vapor or gaseous form: Not applicable
: Organic Substances: Not applicable
: Carcinogenic substances: Not applicable

APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

- : mutagenic: Not applicable
- : Toxic to reproduction: Not applicable
- Volatile organic compounds (VOC) content : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Update: Percent volatile: 75 %
804,34 g/l
VOC content excluding water
- Volatile organic compounds (VOC) content : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Update: Percent volatile: 75 %
639 g/l
VOC content valid only for coating materials used on wood surfaces

Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products

Registration number : EU-0027673-0000

according to Detergents : disinfectants
Regulation EC 648/2004

15.2 Chemical Safety Assessment

SECTION 16: Other information

Full text of H-Statements

- H225 : Highly flammable liquid and vapor.
- H318 : Causes serious eye damage.
- H319 : Causes serious eye irritation.
- H336 : May cause drowsiness or dizziness.

Full text of other abbreviations

- Eye Dam. : Serious eye damage
- Eye Irrit. : Eye irritation
- Flam. Liq. : Flammable liquids
- STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



APESIN HANDACTIVE F

WM 1116199

Order number: 0716199

Version 4.3

Revision Date 15.07.2026

Print Date 16.07.2026

Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Eye Dam. 1	H318
STOT SE 3	H336

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG_EU / EN

500000004889