

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ENERGY UNICHLOR
UFI : GPE9-R0NT-0000-24WR

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Detergents for dishwashers
Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : Tana Chemie GmbH
Rheinallee 96
55120 Mainz
Telephone : +49613196403
Telefax : +4961319642526
E-mail address : Produktsicherheit@werner-mertz.com
Responsible/issuing person
Contact person : Product development / product safety

1.4 Emergency telephone

EU: 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Corrosive to Metals, Category 1	H290: May be corrosive to metals.
Skin corrosion, Category 1	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

Signal Word	:	Danger	
Hazard Statements	:	H290 H314 H410	May be corrosive to metals. Causes severe skin burns and eye damage. Very toxic to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH206	Warning! Do not use together with other products. May release dangerous gases (chlorine).
Precautionary Statements	:	P102 Prevention: P280 Response: P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. Disposal: P501	Keep out of reach of children. Wear protective gloves/ protective clothing/ eye protection/ face protection.
			Dispose of container into the collection of recyclables only when it is completely empty.

Hazardous ingredients which must be listed on the label:

potassium hydroxide
sodium hypochlorite

Additional Labeling:

Safety data sheet available on request.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Aqueous solution
contains

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
potassium hydroxide	1310-58-3 215-181-3 019-002-00-8 01-2119487136-33	Acute Tox. 4; H302 Skin Corr. 1A; H314 Met. Corr. 1; H290 Eye Dam. 1; H318 specific concentration limit Skin Corr. 1A; H314 >= 5 % Skin Corr. 1B; H314 2 - < 5 % Skin Irrit. 2; H315 0,5 - < 2 % Eye Irrit. 2; H319 0,5 - < 2 % Acute toxicity estimate Acute oral toxicity: 500,0 mg/kg	>= 5 - < 10
tetrapotassium pyrophosphate	7320-34-5 230-785-7 01-2119489369-18	Eye Irrit. 2; H319	>= 5 - < 10
Silicic acid, potassium salt	1312-76-1 215-199-1 01-2119456888-17	Eye Irrit. 2; H319 Skin Irrit. 2; H315	>= 5 - < 10
sodium hypochlorite	7681-52-9 017-011-00-1	Met. Corr. 1; H290 Eye Dam. 1; H318 Skin Corr. 1B; H314 STOT SE 3; H335 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH031 M-Factor (Acute aquatic toxicity): 1010 M-Factor (Chronic aquatic toxicity): 11 specific concentration limit EUH031 >= 5 %	>= 3 - < 5

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

SECTION 4: First aid measures

4.1 Description of first-aid measures

- | | | |
|-------------------------|---|---|
| General advice | : | Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance. |
| If inhaled | : | Move to fresh air.
If symptoms persist, call a physician. |
| In case of skin contact | : | Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty. |
| In case of eye contact | : | Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
Protect unharmed eye.
Continue rinsing eyes during transport to hospital. |
| If swallowed | : | Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|----------|---|---------------------------|
| Symptoms | : | corrosive effects |
| Risks | : | No information available. |

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|--|
| Treatment | : | For specialist advice physicians should contact the Poisons Information Service. |
|-----------|---|--|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|------------------------------|---|---|
| Suitable extinguishing media | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
|------------------------------|---|---|

5.2 Special hazards arising from the substance or mixture

- | | | |
|---------------------------------------|---|---|
| Specific hazards during fire fighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : | Chlorine compounds |

5.3 Advice for firefighters

- | | | |
|--|---|---|
| Special protective equipment for fire-fighters | : | In the event of fire, wear self-contained breathing apparatus. |
| Further information | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be |

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Neutralize with acid.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations"., Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store at room temperature in the original container.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

Specific use(s) : Detergents for dishwashers

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
potassium hydroxide	Workers	Inhalation	Long-term local effects	1 mg/m ³
	Consumers	Inhalation	Long-term local effects	1 mg/m ³
tetrapotassium pyrophosphate	Workers	Inhalation	Long-term systemic effects	2,79 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	0,68 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	> 70 mg/kg
Silicic acid, potassium salt	Workers	Inhalation	Long-term systemic effects	5,61 mg/m ³
	Workers	Skin contact	Long-term systemic effects	1,49 mg/kg
	Consumers	Inhalation	Long-term systemic effects	1,38 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0,74 mg/kg
	Consumers	Ingestion	Long-term systemic effects	0,74 mg/kg
sodium hypochlorite, sodium hypochlorite (Solution ...%Cl active), sodium hypochlorite (Solution)	Consumers	Oral	Long-term systemic effects	0,26 mg/kg
	Workers	Inhalation	Long-term exposure, Local effects, Systemic effects	1,55 mg/m ³
	Workers	Inhalation	Short-term exposure, Local effects, Systemic	3,1 mg/m ³

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

			effects	
	Consumers	Inhalation	Long-term exposure, Local effects, Systemic effects	1,55 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
tetrapotassium pyrophosphate	Fresh water	0,05 mg/l
	Sea water	0,005 mg/l
	STP	50 mg/l
	intermittent release	0,5 mg/l
Silicic acid, potassium salt	Fresh water	7,5 mg/l
sodium hypochlorite, sodium hypochlorite (Solution ...%Cl active), sodium hypochlorite (Solution)	Fresh water	0,21 mg/l
	Sea water	0,042 mg/l
	intermittent release	0,26 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Remove and wash contaminated clothing before re-use.

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

Respiratory protection : Not required; except in case of aerosol formation.

Recommended Filter type:

ABEK-P3-filter

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: liquid
Color	: light yellow
Odor	: characteristic
Melting point/freezing point	: No data available
Boiling point/boiling range	: No information available.
Flammability (solid, gas)	: No data available
Flammability (liquids)	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Flash point	: does not flash
Ignition temperature	: No data available
Decomposition temperature	: No data available
pH	: ca. 13,5, 100 % at 20 °C
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Vapor pressure	: No data available
Density	: ca. 1,4 g/cm ³
Relative density	: No data available
Relative vapor density	: No data available
Particle characteristics	: No data available

9.2 Other information

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.
No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
No decomposition if used as directed.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Our company is strongly against animal testing.
Our company does not place any orders for animal testing for the finished product or the ingredients.
However, as a result of EU legislation (REACH Regulation), the manufacturers of ingredients or EU importers are obliged to test ingredients with regard to their effects on human health and the environment before they are brought onto the market. Some of the tests made necessary by this took place decades ago.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

potassium hydroxide

1310-58-3:

Acute oral toxicity : LD50 (Rat): 273 mg/kg

Acute toxicity estimate: 500,0 mg/kg
Method: Converted acute toxicity point estimate

LD50 Oral (Rat, male): 333 mg/kg
Method: OECD Test Guideline 425

tetrapotassium pyrophosphate

7320-34-5:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

LD50 (Mouse): > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1,1 mg/l
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 7.940 mg/kg

LD50 Dermal (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402

Silicic acid, potassium salt

1312-76-1:

Acute oral toxicity : LD50 (Rat): ca. 1,3 g/kg

LD50 Oral (Rat): > 2.000 mg/kg

sodium hypochlorite

7681-52-9:

Acute oral toxicity : LD50 (Mouse): 5.800 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 10.000 mg/kg

Skin corrosion/irritation

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:

potassium hydroxide

1310-58-3:

Result : Corrosive

tetrapotassium pyrophosphate

7320-34-5:

Result : Mild skin irritation

Result : No skin irritation

Silicic acid, potassium salt

1312-76-1:

Result : Skin irritation

Serious eye damage/eye irritation

Product:

Remarks : May cause irreversible eye damage.

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

Components:

potassium hydroxide

1310-58-3:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Corrosive

tetrapotassium pyrophosphate

7320-34-5:

Result : Eye irritation

Silicic acid, potassium salt

1312-76-1:

Result : Eye irritation

Respiratory or skin sensitization

Product:

Remarks : No data available

Components:

potassium hydroxide

1310-58-3:

Species : Guinea pig
Result : Did not cause sensitization on laboratory animals.

Silicic acid, potassium salt

1312-76-1:

Result : Does not cause skin sensitization.

Germ cell mutagenicity

Germ cell mutagenicity : Not Rated

Components:

potassium hydroxide

1310-58-3:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Result: negative

Carcinogenicity : Not Rated

Reproductive toxicity : Not Rated

STOT-single exposure : The substance or mixture is not classified as specific target organ toxicant, single exposure.

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

STOT-repeated exposure : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration toxicity : Not Rated

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

potassium hydroxide

1310-58-3:

Toxicity to fish : (Pimephales promelas (fathead minnow)): 880 mg/l
Exposure time: 96 h
Test Type: static test

LC50 (Gambusia affinis (Mosquito fish)): 80 mg/l
Exposure time: 96 h

LC50 (Poecilia reticulata (guppy)): 165 mg/l
Exposure time: 24 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 45,4 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 660 mg/l
Exposure time: 48 h
Test Type: static test

EC50 (Ceriodaphnia dubia (water flea)): 40,4 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 : 1.337 mg/l
Exposure time: 120 h

Toxicity to microorganisms : EC50 (Photobacterium phosphoreum): 22 mg/l
Exposure time: 15 min

Toxicity to soil dwelling organisms : LC50: 850 mg/kg
Exposure time: 90 d

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

tetrapotassium pyrophosphate

7320-34-5:

- Toxicity to fish : LC0 (Leuciscus idus (Golden orfe)): > 750 mg/l
Exposure time: 48 h

LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 : > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC : > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : (activated sludge): > 1.000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
- Toxicity to fish (Chronic toxicity) : 100 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)
Method: OECD Test Guideline 203

Silicic acid, potassium salt

1312-76-1:

- Toxicity to daphnia and other aquatic invertebrates : EC0 (Daphnia magna (Water flea)): > 500 mg/l
Exposure time: 24 h
- Toxicity to microorganisms : EC0 (Pseudomonas putida): > 10.000 mg/l
Exposure time: 18 h

sodium hypochlorite, sodium hypochlorite (Solution ...%Cl active), sodium hypochlorite (Solution)

7681-52-9:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1,34 mg/l
Exposure time: 96 h

LC50 (Fish): 0,06 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,07 - 0,7 mg/l
Exposure time: 24 h
Test Type: static test

EC50 (Daphnia magna (Water flea)): 0,141 mg/l
Exposure time: 48 h
- M-Factor (Acute aquatic toxicity) : 10

10
- Toxicity to microorganisms : EC50 (Photobacterium phosphoreum): 100 mg/l
Exposure time: 15 min

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

Toxicity to fish (Chronic toxicity) : NOEC: 0,04 mg/l
Species: Menidia peninsulae (tidewater silverside)

M-Factor (Chronic aquatic toxicity) : 1

1

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: The surfactant(s) contained in this preparation complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.

Components:

potassium hydroxide

1310-58-3:

Biodegradability : Result: Biodegradable
Remarks: The methods for determining the biological degradability are not applicable to inorganic substances.

tetrapotassium pyrophosphate

7320-34-5:

Biodegradability : Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

Silicic acid, potassium salt

1312-76-1:

Biodegradability : Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

Components:

potassium hydroxide

1310-58-3:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

tetrapotassium pyrophosphate

7320-34-5:

Bioaccumulation : Remarks: Does not bioaccumulate.

sodium hypochlorite, sodium hypochlorite (Solution ...%Cl active), sodium hypochlorite (Solution)

7681-52-9:

Partition coefficient: n-octanol/water : log Pow: -3,42

12.4 Mobility in soil

No data available

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

potassium hydroxide

1310-58-3:

Assessment : Not very persistent and very bioaccumulative (vPvB).. Not persistent, bioaccumulative, and toxic (PBT).

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

Waste Code : European Waste Catalog
20 01 29*
According to the European Waste Catalog, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : 1760
IMDG : 1760
IATA : 1760

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

14.2 UN proper shipping name

ADR : CORROSIVE LIQUID, N.O.S.
(potassium hydroxide)

IMDG : CORROSIVE LIQUID, N.O.S.
(potassium hydroxide)

IATA : Corrosive liquid, n.o.s.

14.3 Transport hazard class(es)

ADR : 8

IMDG : 8

IATA : 8

14.4 Packing group

ADR

Classification Code : C9

Packaging group : II

Hazard Identification Number : 80

Labels : 8

Tunnel restriction code : (E)

IMDG

Packaging group : II

Labels : 8

EmS Number : F-A, S-B

IATA

(Cargo) : Corrosive liquid, n.o.s.

Packaging group : II

Labels : 8

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

For personal protection see section 8.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the : See Annex XVII to Regulation (EC) no

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

market and use of certain dangerous substances, mixtures and articles (Annex XVII) 1907/2006 for Conditions of restriction

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
E1	ENVIRONMENTAL HAZARDS	100 000067	200 000067

TA Luft List (Germany) :

- Total dust: Not applicable
- Inorganic substances in powdered form: Not applicable
- Inorganic substances in vapor or gaseous form: Not applicable
- Organic Substances: Not applicable
- Carcinogenic substances: Not applicable
- mutagenic: Not applicable
- Toxic to reproduction: Not applicable

Volatile organic compounds (VOC) content :

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

Update: Percent volatile: 3,25 %
419,26 g/l
VOC content excluding water

Volatile organic compounds (VOC) content :

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

Update: Percent volatile: 3,25 %
45,5 g/l
VOC content valid only for coating materials used on wood surfaces

according to Detergents Regulation EC 648/2004 :

15 - <30% phosphates, <5% phosphonates, chlorine-based bleaching agents

15.2 Chemical Safety Assessment

There is no data available for this product.

SECTION 16: Other information

Full text of H-Statements

H290	:	May be corrosive to metals.
H302	:	Harmful if swallowed.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H335	:	May cause respiratory irritation.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
EUH031	:	Contact with acids liberates toxic gas.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Met. Corr.	:	Corrosive to Metals
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Met. Corr. 1	H290
Skin Corr. 1	H314
Eye Dam. 1	H318
Aquatic Acute 1	H400
Aquatic Chronic 2	H411

Classification procedure:

On basis of test data.
Based on product data or assessment
Based on product data or assessment
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG_EU / EN

ENERGY UNICHLOR

WM 1113266

Order number: 0713266

Version 4.2

Revision Date 16.07.2026

Print Date 16.07.2026

500000000837