

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : QUICKSTRIP turbo
UFI : JM88-50S2-C004-8S5N

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Cleaning agent

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : Tana Chemie GmbH
Rheinallee 96
55120 Mainz
Telephone : +49613196403
Telefax : +4961319642526
E-mail address : Produktsicherheit@werner-mertz.com
Responsible/issuing person
Contact person : Product development / product safety

1.4 Emergency telephone

EU: 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Corrosive to Metals, Category 1	H290: May be corrosive to metals.
Skin corrosion, Category 1	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

Signal Word	:	Danger	
Hazard Statements	:	H290 H314 H317 H335	May be corrosive to metals. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause respiratory irritation.
Precautionary Statements	:	P102 Prevention: P261 P272 P280 Response: P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Disposal: P501	Keep out of reach of children. Avoid breathing spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face protection. Immediately call a POISON CENTER/ doctor. Dispose of container into the collection of recyclables only when it is completely empty.

Hazardous ingredients which must be listed on the label:

2-aminoethanol
benzyl alcohol
Sodium metasilicate,
pentahydrate

Safety data sheet available on request.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Aqueous solution

Components

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-aminoethanol	141-43-5 205-483-3 603-030-00-8 01-2119486455-28	Acute Tox. 4; H332 Acute Tox. 4; H312 Acute Tox. 4; H302 Skin Corr. 1B; H314 STOT SE 3; H335 Aquatic Chronic 3; H412 Eye Dam. 1; H318 specific concentration limit STOT SE 3; H335 ≥ 5 % Acute toxicity estimate Acute oral toxicity: 500,0 mg/kg Acute inhalation toxicity: 11 mg/l Acute dermal toxicity: 1.100 mg/kg	≥ 10 - < 15
benzyl alcohol	100-51-6 202-859-9 603-057-00-5 01-2119492630-38	Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity estimate Acute oral toxicity: 1.230 mg/kg 1.200 mg/kg Acute inhalation toxicity (dust/mist): 4,188 mg/l	≥ 5 - < 10
Sodium metasilicate, pentahydrate	10213-79-3 01-2119449811-37	Met. Corr. 1; H290 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335	≥ 5 - < 10
sodium p-cumenesulphonate	15763-76-5 239-854-6 01-2119489411-37	Eye Irrit. 2; H319	≥ 3 - < 5

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
If symptoms persist, call a physician.

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

- | | | |
|-------------------------|---|---|
| In case of skin contact | : | Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty. |
| In case of eye contact | : | Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
Protect unharmed eye.
Continue rinsing eyes during transport to hospital. |
| If swallowed | : | Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|----------|---|--|
| Symptoms | : | corrosive effects
Allergic reactions
Irritation |
| Risks | : | No information available.

May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
Causes severe burns. |

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|--|
| Treatment | : | For specialist advice physicians should contact the Poisons Information Service. |
|-----------|---|--|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|------------------------------|---|---|
| Suitable extinguishing media | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
|------------------------------|---|---|

5.2 Special hazards arising from the substance or mixture

- | | | |
|---------------------------------------|---|---|
| Specific hazards during fire fighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : | No hazardous combustion products are known |

5.3 Advice for firefighters

- | | | |
|--|---|---|
| Special protective equipment for fire-fighters | : | In the event of fire, wear self-contained breathing apparatus. |
| Further information | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Neutralize with acid.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations"., Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors or spray mist.
Avoid contact with skin and eyes.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store at room temperature in the original container.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Cleaning agent

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-aminoethanol	Not Assigned	TWA	1 ppm 2,5 mg/m ³	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		STEL	3 ppm 7,6 mg/m ³	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
2-aminoethanol	Consumers	Skin contact	Long-term systemic effects	0,24 mg/kg
	Consumers	Inhalation	Long-term local effects	2 mg/m ³
	Consumers	Oral	Long-term systemic effects	1,5 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	3 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	1,5 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	1 mg/m ³
	Workers	Inhalation	Long-term local effects	0,51 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	0,18 mg/m ³
	Consumers	Inhalation	Long-term local effects	0,28 mg/m ³
benzyl alcohol	Workers	Inhalation	Long-term systemic	22 mg/m ³

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

			effects	
	Workers	Inhalation	Acute systemic effects	110 mg/m3
	Workers	Skin contact	Long-term systemic effects	8 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	40 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	5,4 mg/m3
	Consumers	Inhalation	Acute systemic effects	27 mg/m3
	Consumers	Skin contact	Long-term systemic effects	4 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	20 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	20 mg/kg bw/day
Sodiumsilicate, pentahydrate, Silicic acid (H ₂ SiO ₃), disodium salt, pentahydrate, Sodium silicate pentahydrate	Consumers	Oral	Long-term systemic effects	0,74 mg/kg
	Workers	Inhalation	Long-term systemic effects	6,22 mg/m3
	Consumers	Inhalation	Long-term systemic effects	1,55 mg/m3
	Workers	Skin contact	Long-term systemic effects	1,49 mg/kg
	Consumers	Skin contact	Long-term systemic effects	0,74 mg/kg
2-(2-ethoxyethoxy)ethanol	Workers	Skin contact	Long-term systemic effects	50 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	25 mg/kg bw/day

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

	Workers	Inhalation	Long-term local effects	37 mg/m3
	Consumers	Inhalation	Long-term systemic effects	18,3 mg/m3
	Consumers	Inhalation	Long-term local effects	9 mg/m3
	Workers	Inhalation	Long-term local effects	18 mg/m3
sodium p-cumenesulphonate	Consumers	Skin contact	Long-term systemic effects	3,8 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	13,2 mg/m3
	Consumers	Ingestion	Long-term systemic effects	3,8 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	6,6 mg/m3
	Consumers	Inhalation	Long-term local effects	0,048 mg/cm2
	Workers	Skin contact	Long-term systemic effects	7,6 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	53,6 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-aminoethanol	Fresh water	0,07 mg/l
	Sea water	0,007 mg/l
	STP	100 mg/l
	intermittent release	0,028 mg/l
	Fresh water sediment	0,357 mg/kg
	Sea sediment	0,0357 mg/kg
	Soil	1,29 mg/kg
benzyl alcohol	Fresh water	1 mg/l
	Sea water	0,1 mg/l
	intermittent release	2,3 mg/l
	STP	39 mg/l

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

	Fresh water sediment	5,27 mg/kg
	Sea sediment	0,527 mg/kg
	Soil	0,456 mg/kg
Sodiumsilicate, pentahydrate, Silicic acid (H ₂ SiO ₃), disodium salt, pentahydrate, Sodium silicate pentahydrate	Fresh water	7,5 mg/l
	Sea water	1 mg/l
	intermittent release	7,5 mg/l
	STP	1000 mg/l
2-(2-ethoxyethoxy)ethanol	Fresh water	0,74 mg/l
	Sea water	0,074 mg/l
	Fresh water sediment	2,47 mg/kg
	Sea sediment	0,274 mg/kg
	Soil	0,15 mg/kg
	STP	500 mg/l
	intermittent release	10 mg/l
sodium p-cumenesulphonate	Fresh water	0,23 mg/l
	STP	100 mg/l
	intermittent release	2,3 mg/l
	Fresh water sediment	0,862 mg/kg
	Sea sediment	0,0862 mg/kg
	Soil	0,037 mg/kg
	Fresh water	0,1 mg/l
	intermittent release	1 mg/l
	Sea water	0,01 mg/l
	Fresh water sediment	0,372 mg/kg dry weight (d.w.)
	Sea sediment	0,0372 mg/kg dry weight (d.w.)

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

	Soil	0,016 mg/kg dry weight (d.w.)
--	------	-------------------------------

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Remove and wash contaminated clothing before re-use.

Respiratory protection : Not required; except in case of aerosol formation.

Recommended Filter type:

ABEK-P3-filter

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : colorless

Odor : characteristic

Melting point/freezing point : No data available

Boiling point/boiling range : No information available.

Flammability (solid, gas) : No data available

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

Flammability (liquids)	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Flash point	: No data available
Ignition temperature	: No data available
Decomposition temperature	: No data available
pH	: ca. 13,1, 100 % at 20 °C
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Vapor pressure	: No data available
Density	: ca. 1,059 g/cm ³
Relative density	: No data available
Relative vapor density	: No data available
Particle characteristics	: No data available

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.
No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
No decomposition if used as directed.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Our company is strongly against animal testing.

Our company does not place any orders for animal testing for the finished product or the ingredients.

However, as a result of EU legislation (REACH Regulation), the manufacturers of ingredients or EU importers are obliged to test ingredients with regard to their effects on human health and the environment before they are brought onto the market. Some of the tests made necessary by this took place decades ago.

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

2-aminoethanol

141-43-5:

Acute oral toxicity : LD50 Oral (Rat): 1.515 mg/kg
Method: OECD Test Guideline 401

Acute toxicity estimate: 500,0 mg/kg
Method: Converted acute toxicity point estimate

LD50 (Rat): 1.089 mg/kg
Method: OECD Test Guideline 401

LD50 (Rat): 1.750 - 2.050 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1,3 mg/l
Exposure time: 6 h
Remarks: Harmful by inhalation.

LC50 (Rat): 1,487 mg/l
Exposure time: 4 h

Acute toxicity estimate: 11 mg/l

LC50 (Rat): 1,3 mg/l
Exposure time: 4 h

LC50 (Rat): 136 mg/l
Test atmosphere: Mist

Acute dermal toxicity : LD50 Dermal (Rabbit): 2.504 mg/kg
Method: OECD Test Guideline 402

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

Acute toxicity estimate: 1.100 mg/kg
Method: Converted acute toxicity point estimate

LD50 (Rabbit): 1.000 mg/kg

benzyl alcohol

100-51-6:

Acute oral toxicity : LD50 (Rat): 1.230 mg/kg

LD50 Oral (Rabbit): 1.040 mg/kg

LD50 Oral (Guinea pig): 2.500 mg/kg

LD50 Oral (Rat, male): 1.620 mg/kg

Acute toxicity estimate: 1.230 mg/kg

(Rat, male): 1.045 mg/kg

Acute toxicity estimate: 1.200 mg/kg
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Acute inhalation toxicity : LC50 (Rat): 4,178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

LC50 (Rat): 20 mg/l
Exposure time: 4 h

Acute toxicity estimate: 4,188 mg/l
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): 2.000 mg/kg

LD50 Dermal: 2.500 mg/kg

Sodium metasilicate, pentahydrate

10213-79-3:

Acute oral toxicity : LD50 (Rat): 1.152 - 1.349 mg/kg

Acute inhalation toxicity : LC50 (Rat): 2,06 mg/l

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

sodium p-cumenesulphonate

15763-76-5:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 5 mg/l
Exposure time: 232 min

LC50 (Rat): 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg
LD50 (Rabbit): > 2.000 - 5.000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:

2-aminoethanol

141-43-5:

Species : Rabbit
Assessment : Corrosive
Method : OECD Test Guideline 404
Result : Corrosive

benzyl alcohol

100-51-6:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Mild skin irritation

sodium p-cumenesulphonate

15763-76-5:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

2-aminoethanol

141-43-5:

Species : Rabbit
Assessment : Risk of serious damage to eyes.
Method : OECD Test Guideline 405
Result : Risk of serious damage to eyes.

benzyl alcohol

100-51-6:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Moderate eye irritation

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

sodium p-cumenesulphonate

15763-76-5:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	Moderate eye irritation
Remarks	:	Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Product:

Remarks	:	Causes sensitization.
---------	---	-----------------------

Components:

2-aminoethanol

141-43-5:

Test Type	:	Maximization Test
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	Did not cause sensitization on laboratory animals.

benzyl alcohol

100-51-6:

Test Type	:	Draize Test
Species	:	Guinea pig
Result	:	negative
Test Type	:	Local lymph node assay (LLNA)
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative
Test Type	:	Maximization Test
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

sodium p-cumenesulphonate

15763-76-5:

Test Type	:	Buehler Test
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	Did not cause sensitization on laboratory animals.

Germ cell mutagenicity

Not classified due to lack of data.

Germ cell mutagenicity	:	Not Rated
------------------------	---	-----------

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

Components:

benzyl alcohol

100-51-6:

- Genotoxicity in vitro : Test Type: Micronucleus test
Test system: human lymphoblastoid cells
Method: OECD Test Guideline 487
Result: negative
- Test Type: Ames test
Test system: TA98
Method: OECD Test Guideline 471
Result: negative
- Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse (males)
Method: OECD Test Guideline 474
Remarks: negative
- Test Type: in vivo assay
Species: Drosophila melanogaster (vinegar fly) (male)
Method: OECD Test Guideline 477
Remarks: negative

sodium p-cumenesulphonate

15763-76-5:

- Genotoxicity in vitro : Result: negative
- Genotoxicity in vivo : Remarks: negative

Carcinogenicity

Not classified due to lack of data.

- Carcinogenicity : Not Rated

Components:

sodium p-cumenesulphonate

15763-76-5:

- Species : Rat
Application Route : Dermal
Exposure time : 2 Years
Activity duration : 5 h
Method : OECD Test Guideline 453
Result : no increase in tumors observed
Remarks : Information taken from reference works and the literature.
- Carcinogenicity - Assessment : Animal testing did not show any carcinogenic effects.

Reproductive toxicity

Not classified due to lack of data.

- Reproductive toxicity : Not Rated

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

STOT-single exposure

May cause respiratory irritation.

STOT-single exposure : The substance or mixture is not classified as specific target organ toxicant, single exposure.

Components:

2-aminoethanol

141-43-5:

Target Organs : Respiratory Tract
Assessment : May cause respiratory irritation.

sodium p-cumenesulphonate

15763-76-5:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT-repeated exposure

Not classified due to lack of data.

STOT-repeated exposure : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Components:

sodium p-cumenesulphonate

15763-76-5:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

2-aminoethanol

141-43-5:

Species : Rat, male
NOAEL : 1.000 mg/kg

Species : Rat, female
NOAEL : 300 mg/kg

benzyl alcohol

100-51-6:

Species : Rat, male and female
NOEC : 1072 mg/l
Application Route : Inhalation
Test atmosphere : dust/mist
Method : OECD Test Guideline 412
GLP : yes

sodium p-cumenesulphonate

15763-76-5:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

Species : Rat
NOAEL : 763 mg/kg
Application Route : Oral
Target Organs : Cardio-vascular system

Species : Mouse
NOAEL : 440 mg/kg
LOAEL : 1.300 mg/kg
Application Route : Dermal
Method : OECD Test Guideline 411
Target Organs : Skin

Aspiration toxicity

Not classified due to lack of data.

Aspiration toxicity : Not Rated

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-aminoethanol

141-43-5:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 150 mg/l
Exposure time: 96 h

LC50 (Lepomis macrochirus (Bluegill sunfish)): 329 mg/l
Exposure time: 96 h

LC50 (Cyprinus carpio (Carp)): 349 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203

LC50 (Carassius auratus (goldfish)): 170 mg/l
Exposure time: 96 h
Test Type: static test

LC50 (Leuciscus idus (Golden orfe)): 224 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

- LC50 (*Oncorhynchus mykiss* (rainbow trout)): 105 mg/l
Exposure time: 96 h
- (*Oryzias latipes* (Orange-red killifish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 27,04 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
- NOEC (*Daphnia magna* (Water flea)): 0,85 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
- EC50 (*Daphnia magna* (Water flea)): 65 mg/l
Exposure time: 48 h
Test Type: static test
Method: EG 84/449
- Toxicity to algae/aquatic plants : EC50 (*Selenastrum capricornutum*): 2,8 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201
- EC50 (*Scenedesmus subspicatus*): 22 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
- NOEC (*Selenastrum capricornutum*): 1 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201
- EC50 (*Scenedesmus subspicatus*): 15 mg/l
Exposure time: 72 h
- EC50 (*Selenastrum capricornutum*): 2,5 mg/l
Exposure time: 72 h
- EC10 (*Pseudokirchneriella subcapitata* (green algae)): 0,7 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC20 (activated sludge): > 1.000 mg/l
Exposure time: 0,5 h
Method: OECD Test Guideline 209
- EC50 (*Pseudomonas putida*): 110 mg/l
Exposure time: 16 h
Method: DIN 38412
- EC50 (activated sludge): > 1.000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
- EC50 (*Pseudomonas putida*): 110 mg/l
Exposure time: 17 h

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

Test Type: Respiration inhibition

Toxicity to fish (Chronic toxicity) : NOEC: 1,24 mg/l
Exposure time: 41 d
Species: *Oryzias latipes* (Orange-red killifish)

Toxicity to soil dwelling organisms : EC50: 4.033 mg/kg
Exposure time: 63 d
Species: *Eisenia fetida* (earthworms)

benzyl alcohol

100-51-6:

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): 460 mg/l
Exposure time: 96 h
Test Type: static test
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 400 mg/l
Exposure time: 24 h

EC100 (*Daphnia magna* (Water flea)): 500 mg/l
Exposure time: 48 h

LC50 (*Daphnia magna* (Water flea)): 360 mg/l
Exposure time: 48 h

EC50 (*Daphnia magna* (Water flea)): 230 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

EC50 (*Daphnia magna* (Water flea)): 66 mg/l
Method: OECD Test Guideline 211
GLP: yes

NOEC (*Daphnia magna* (Water flea)): 51 mg/l
Method: OECD Test Guideline 211
GLP: yes

Toxicity to algae/aquatic plants : EC0 (*Scenedesmus quadricauda* (Green algae)): 640 mg/l
Exposure time: 96 h

NOEC (*Pseudokirchneriella subcapitata* (green algae)): 310 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

IC50 (*Pseudokirchneriella subcapitata* (green algae)): 770 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (*Pseudokirchneriella subcapitata* (green algae)): 770 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (*Pseudomonas putida*): 658 mg/l
Exposure time: 16 h
Test Type: Cell multiplication inhibition test
Method: DIN 38412

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

IC50 (Natural microorganism): 390 mg/l
Exposure time: 24 h
Method: ISO 8192

(Bacteria): 390 mg/l
Exposure time: 24 h
Analytical monitoring: no
Method: OECD Test Guideline 209
GLP: no

IC50 (Bacteria): 2.100 mg/l
Exposure time: 49 h
Test Type: Respiration inhibition
Analytical monitoring: no
Method: OECD Test Guideline 209
GLP: no

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 51 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
GLP: yes

Sodiumsilicate, pentahydrate, Silicic acid (H₂SiO₃), disodium salt, pentahydrate, Sodium silicate pentahydrate

10213-79-3:

Toxicity to fish : LC50 (Brachydanio rerio): 210 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.700 mg/l
Exposure time: 48 h

sodium p-cumenesulphonate

15763-76-5:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: static test

LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 96 h
Test Type: static test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

EC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC10 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (activated sludge): > 1.000 mg/l
Exposure time: 3 h
Test Type: Respiration inhibition
Method: OECD Test Guideline 209

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: The surfactant(s) contained in this preparation complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.

Components:

2-aminoethanol

141-43-5:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Readily biodegradable.
Biodegradation: > 90 %
Exposure time: 21 d
Method: OECD 301 A

Result: rapidly biodegradable

Biodegradation: 90 - 100 %

Method: OECD 301 F

Biochemical Oxygen Demand (BOD) : 800 mg/g
Incubation time: 5 d

ThOD : 1,31 g/g

benzyl alcohol

100-51-6:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 90 %
Exposure time: 30 d
Method: OECD 301 D

Test Type: aerobic

Result: Readily biodegradable.

Biodegradation: 95 - 97 %

Exposure time: 21 d

Method: OECD 301 A

Test Type: aerobic

Result: rapidly biodegradable

Biodegradation: 92 - 96 %

Exposure time: 14 d

Method: OECD 301 C

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

sodium p-cumenesulphonate

15763-76-5:

Biodegradability : Test Type: aerobic
Result: Readily biodegradable.
Biodegradation: > 60 %
Exposure time: 28 d
Method: OECD 301 B

12.3 Bioaccumulative potential

Components:

2-aminoethanol

141-43-5:

Bioaccumulation : Bioconcentration factor (BCF): 1

Remarks: Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

Partition coefficient: n-octanol/water : log Pow: -1,91 (25 °C)
Method: OECD Test Guideline 107

log Pow: -2,3 (25 °C)
pH: 6,8 - 7,3
Method: OECD Test Guideline 107

benzyl alcohol

100-51-6:

Bioaccumulation : Bioconcentration factor (BCF): 1

Partition coefficient: n-octanol/water : log Pow: 1,10

sodium p-cumenesulphonate

15763-76-5:

Bioaccumulation : Bioconcentration factor (BCF): 3,16
Remarks: Bioaccumulation is unlikely.

12.4 Mobility in soil

Components:

2-aminoethanol

141-43-5:

Distribution among environmental compartments : Medium: Soil
Koc: 5
Remarks: Highly mobile in soils

Stability in soil : Remarks: Will not adsorb on soil.

benzyl alcohol

100-51-6:

Distribution among environmental compartments : Koc: 15
Remarks: Highly mobile in soils

QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

sodium p-cumenesulphonate

15763-76-5:

Distribution among environmental compartments : Koc: 1,25
Method: Calculation method
Remarks: Information taken from reference works and the literature.

Stability in soil : Remarks: Not expected to adsorb on soil.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

2-aminoethanol

141-43-5:

Assessment : Not very persistent and very bioaccumulative (vPvB).. Not persistent, bioaccumulative, and toxic (PBT).

benzyl alcohol

100-51-6:

Assessment : Not persistent, bioaccumulative, and toxic (PBT).. Not very persistent and very bioaccumulative (vPvB).

sodium p-cumenesulphonate

15763-76-5:

Assessment : Not persistent, bioaccumulative, and toxic (PBT).. Not very persistent and very bioaccumulative (vPvB).

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
In accordance with local and national regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.
Waste Code	European Waste Catalog 20 01 29* According to the European Waste Catalog, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	: 1760
IMDG	: 1760
IATA	: 1760

14.2 UN proper shipping name

ADR	: CORROSIVE LIQUID, N.O.S. (2-aminoethanol, Sodium metasilicate, pentahydrate)
IMDG	: CORROSIVE LIQUID, N.O.S. (Ethanolamine, Sodium metasilicate, pentahydrate)
IATA	: Corrosive liquid, n.o.s.

14.3 Transport hazard class(es)

ADR	: 8
IMDG	: 8
IATA	: 8

14.4 Packing group

ADR	
Classification Code	: C9
Packaging group	: III
Hazard Identification Number	: 80
Labels	: 8
Tunnel restriction code	: (E)
IMDG	
Packaging group	: III
Labels	: 8
EmS Number	: F-A, S-B
IATA	
(Cargo)	: Corrosive liquid, n.o.s.
Packaging group	: III
Labels	: 8

14.5 Environmental hazards

ADR	
Environmentally hazardous	: no
IMDG	
Marine pollutant	: no
IATA	
Environmentally hazardous	: no

14.6 Special precautions for user

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

For personal protection see section 8.

14.7 Maritime transport in bulk according to IMO instruments
Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

: Directive 96/82/EC does not apply

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : Not applicable

TA Luft List (Germany) : Total dust: Not applicable
: Inorganic substances in powdered form: Not applicable
: Inorganic substances in vapor or gaseous form: Not applicable
: Organic Substances: : portionClass 1: 17 %
: Carcinogenic substances: Not applicable
: mutagenic: Not applicable
: Toxic to reproduction: Not applicable

Volatile organic compounds (VOC) content : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Update: Percent volatile: 14 %

according to Detergents Regulation EC 648/2004 : perfumes, BENZYL ALCOHOL

15.2 Chemical Safety Assessment

There is no data available for this product.

SECTION 16: Other information

Full text of H-Statements

H290 : May be corrosive to metals.
H302 : Harmful if swallowed.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.
H317 : May cause an allergic skin reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Met. Corr.	:	Corrosive to Metals
Skin Corr.	:	Skin corrosion
Skin Sens.	:	Skin sensitization
STOT SE	:	Specific target organ toxicity - single exposure
2006/15/EC	:	Europe. Indicative occupational exposure limit values
2006/15/EC / TWA	:	Limit Value - eight hours
2006/15/EC / STEL	:	Short term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Met. Corr. 1	H290
Skin Corr. 1	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
STOT SE 3	H335

Classification procedure:

Calculation method
Based on product data or assessment
Based on product data or assessment
Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



QUICKSTRIP turbo

WM 1304741

Order number: 0404741

Version 9.2

Revision Date 11.07.2026

Print Date 14.07.2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG_EU / EN

500000000921