

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SANET EXTREME F
UFI : VEFC-R06Y-V00R-MPVW

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Cleaning agent
Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : Tana Chemie GmbH
Rheinallee 96
55120 Mainz
Telephone : +49613196403
Telefax : +4961319642526
E-mail address : Produktsicherheit@werner-mertz.com
Responsible/issuing person
Contact person : Product development / product safety

1.4 Emergency telephone

EU: 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Corrosive to Metals, Category 1 H290: May be corrosive to metals.
Skin corrosion, Category 1 H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1 H318: Causes serious eye damage.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Danger
Hazard Statements : H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
Precautionary Statements : P102 Keep out of reach of children.
Prevention:

SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P310

Disposal:

P501 Dispose of container into the collection of recyclables only when it is completely empty.

Hazardous ingredients which must be listed on the label:

methanesulphonic acid
l-(+)-lactic acid
Alcohols, C12-14, ethoxylated
(7 EO)

Safety data sheet available on request.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
methanesulphonic acid	75-75-2 200-898-6 607-145-00-4 01-2119491166-34	Skin Corr. 1B; H314 Met. Corr. 1; H290 Acute Tox. 4; H302 Acute Tox. 4; H312 STOT SE 3; H335 Eye Dam. 1; H318	>= 5 - < 10
l-(+)-lactic acid	79-33-4 201-196-2 607-743-00-5 01-2119474164-39	Skin Corr. 1C; H314 Eye Dam. 1; H318 specific concentration	>= 3 - < 5

SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

		limit Skin Irrit. 2; H315 3 - < 5 % Eye Dam. 1; H318 >= 3 % Eye Irrit. 2; H319 1 - < 3 % Skin Corr. 1C; H314 >= 5 %	
Alcohols, C12-14, ethoxylated (7 EO)	68439-50-9 500-213-3	Acute Tox. 4; H302 Eye Dam. 1; H318 Aquatic Chronic 3; H412 M-Factor (Acute aquatic toxicity): 1 specific concentration limit Eye Dam. 1; H318 > 10 % Eye Irrit. 2; H319 > 1 - 10 %	>= 1 - < 2,5

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
Protect unharmed eye.
Continue rinsing eyes during transport to hospital.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : corrosive effects
- Risks : Causes serious eye damage.

SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

Causes severe burns.

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : For specialist advice physicians should contact the Poisons Information Service.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Neutralize with chalk, alkali solution or ammonia.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations"., Refer to section 15 for specific national regulation.

SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store at room temperature in the original container.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
methanesulphonic acid	Workers	Inhalation	Long-term local effects	2,89 mg/m ³
	Workers	Inhalation	Long-term systemic effects	19,44 mg/kg
	Workers	Skin contact	Long-term systemic effects	19,44 mg/kg
	Consumers	Inhalation	Long-term systemic effects	1,44 mg/kg
	Consumers	Inhalation	Acute systemic effects	1,44 mg/kg
	Consumers	Skin contact	Long-term systemic effects	8,33 mg/kg
	Workers	Inhalation	Long-term systemic effects	6,76 mg/m ³

SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

	Consumers	Ingestion	Long-term systemic effects	8,33 mg/kg
	Consumers	Inhalation	Long-term local effects	1,73 mg/m ³
	Workers	Inhalation	Long-term exposure	0,7 mg/m ³
	Consumers	Inhalation	Long-term local effects	0,42 mg/m ³
I-(+)-lactic acid	Workers	Inhalation	Short-term exposure, Local effects	592 mg/m ³
	Consumers	Ingestion	Short-term exposure, Systemic effects	35,4 mg/kg
	Consumers	Inhalation	Short-term exposure, Local effects	296 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
methanesulphonic acid	Fresh water	0,012 mg/l
	Sea water	0,0012 mg/l
	Fresh water sediment	0,0251 mg/kg
	Soil	0,00183 mg/kg
	Intermittent use/release	0,12 mg/l
	Sewage treatment plant	100 mg/l
I-(+)-lactic acid	Fresh water	1,3 mg/l
	STP	10 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace

SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

conditions (mechanical strain, duration of contact).

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Remove and wash contaminated clothing before re-use.

Respiratory protection : Not required; except in case of aerosol formation.

Recommended Filter type:

ABEK-P3-filter

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: liquid
Color	: colorless
Odor	: characteristic
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flammability (solid, gas)	: No data available
Flammability (liquids)	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Flash point	: does not flash
Ignition temperature	: No data available
Decomposition temperature	: No data available
pH	: ca. 0,4, 100 % at 20 °C
Viscosity, dynamic	: 1 mPa.s at 20 °C
Viscosity, kinematic	: No data available
Water solubility	: completely soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available

SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

Vapor pressure : No data available
Density : 1,039 g/cm³ at 20 °C

Relative density : No data available
Relative vapor density : No data available
Particle characteristics : No data available

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.
No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
No decomposition if used as directed.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Our company is strongly against animal testing.
Our company does not place any orders for animal testing for the finished product or the ingredients.
However, as a result of EU legislation (REACH Regulation), the manufacturers of ingredients or EU importers are obliged to test ingredients with regard to their effects on human health and the environment before they are brought onto the market. Some of the tests made necessary by this took place decades ago.

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

Components:

methanesulphonic acid

75-75-2:

- Acute oral toxicity : LD50 Oral (Rat): 200 mg/kg
LD50 Oral (Rat): 649 mg/kg
- Acute inhalation toxicity : LC0 (Mouse): > 1,88 mg/l
Exposure time: 1 h
LC0 (Rat): 0,74 mg/l
Exposure time: 6 h
- Acute dermal toxicity : LD50 Dermal (Rabbit): < 2.000 mg/kg

l-(+)-lactic acid

79-33-4:

- Acute oral toxicity : LD50 (Rat): 3.730 mg/kg
LD50 (Mouse): 4.875 mg/kg
LD50 Oral (Guinea pig): 1.810 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 7,94 mg/l
Exposure time: 4 h
- Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Alcohols, C12-14, ethoxylated (7 EO)

68439-50-9:

- Acute oral toxicity : LD50 Oral (Rat): 300 - 2.000 mg/kg
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Product:

- Remarks : Extremely corrosive and destructive to tissue.

Components:

methanesulphonic acid

75-75-2:

- Result : Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

- Remarks : May cause irreversible eye damage.

SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

Components:

methanesulphonic acid

75-75-2:

Result : Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Product:

Remarks : No data available

Germ cell mutagenicity

Not classified due to lack of data.

Germ cell mutagenicity : Not Rated

Components:

Alcohols, C12-14, ethoxylated (7 EO)

68439-50-9:

Genotoxicity in vitro : Test Type: Ames test
Result: negative

Carcinogenicity

Not classified due to lack of data.

Carcinogenicity : Not Rated

Reproductive toxicity

Not classified due to lack of data.

Reproductive toxicity : Not Rated

STOT-single exposure

Not classified due to lack of data.

STOT-single exposure : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT-repeated exposure

Not classified due to lack of data.

STOT-repeated exposure : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration toxicity

Not classified due to lack of data.

Aspiration toxicity : Not Rated

SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

methanesulphonic acid

75-75-2:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

LC50 (Cyprinodon variegatus (sheepshead minnow)): > 10.000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 10 - 100 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC20 (activated sludge): > 1.000 mg/l
Exposure time: 0,5 h
Method: ISO 8192

l-(+)-lactic acid

79-33-4:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 130 mg/l
Exposure time: 96 h

LC50 (Fish): 320 mg/l
Exposure time: 48 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 130 mg/l
Exposure time: 48 h

SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

- EC50 (*Daphnia pulex* (Water flea)): 240 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : EC50 (*Selenastrum capricornutum*): 3.500 mg/l
- ErC50 (*Pseudokirchneriella subcapitata* (microalgae)): 2.800 mg/l
Exposure time: 72 h
- Toxicity to microorganisms : EC50 : > 100 mg/l
Exposure time: 3 h

Alcohols, C12-14, ethoxylated (7 EO), Alcohols, C12-14, ethoxylated

68439-50-9:

- Toxicity to fish : LC50 (*Cyprinus carpio* (Carp)): > 1 - 10 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: OECD Test Guideline 203
- LC50 (Fish): > 1 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 1 - 10 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (*Desmodesmus subspicatus* (green algae)): 1 - 10 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
- EC10 (*Desmodesmus subspicatus* (green algae)): 0,1 - 1 mg/l
Exposure time: 72 h
Test Type: static test
- M-Factor (Acute aquatic toxicity) : 1
- Toxicity to microorganisms : EC50 (Bacteria): 140 mg/l
- Toxicity to soil dwelling organisms : 220 mg/kg
Species: *Eisenia fetida* (earthworms)
- Plant toxicity : 10 mg/l
Species: *Lepidium sativum* (cress)
Method: see user defined free text

12.2 Persistence and degradability

Components:

methanesulphonic acid

75-75-2:

- Biodegradability : Result: rapidly biodegradable
Biodegradation: > 99 %
Exposure time: 28 d

l-(+)-lactic acid

79-33-4:

SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

Biodegradability : Result: rapidly biodegradable

Biochemical Oxygen Demand (BOD) : 450 mg/g
Incubation time: 5 d
600 mg/g
Incubation time: 20 d

Chemical Oxygen Demand (COD) : 900 mg/g

ThOD : 1.067 mg/g

Alcohols, C12-14, ethoxylated (7 EO), Alcohols, C12-14. ethoxylated 68439-50-9:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD 301 A

Result: rapidly biodegradable
Biodegradation: > 60 %
Exposure time: 28 d
Method: OECD 301 B

12.3 Bioaccumulative potential

Components:

methanesulphonic acid

75-75-2:

Partition coefficient: n-octanol/water : log Pow: -2,38

12.4 Mobility in soil

Components:

methanesulphonic acid

75-75-2:

Distribution among environmental compartments : Koc: 1
Remarks: Highly mobile in soils

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. In accordance with local and national regulations.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.
Waste Code	European Waste Catalog 20 01 29* According to the European Waste Catalog, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	: 3265
IMDG	: 3265
IATA	: 3265

14.2 UN proper shipping name

ADR	: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (methanesulphonic acid)
IMDG	: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (methanesulphonic acid)
IATA	: Corrosive liquid, acidic, organic, n.o.s.

14.3 Transport hazard class(es)

ADR	: 8
IMDG	: 8
IATA	: 8

14.4 Packing group

ADR	
Classification Code	: C3
Packaging group	: III
Hazard Identification Number	: 80
Labels	: 8
Tunnel restriction code	: (E)
IMDG	
Packaging group	: III
Labels	: 8
EmS Number	: F-A, S-B
IATA	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

(Cargo) : Corrosive liquid, acidic, organic, n.o.s.
(Passenger) : Corrosive liquid, acidic, organic, n.o.s.
Packaging group : III
Labels : 8

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

For personal protection see section 8.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : Not applicable

TA Luft List (Germany) : Total dust: Not applicable
: Inorganic substances in powdered form: Not applicable
: Inorganic substances in vapor or gaseous form: Not applicable
: Organic Substances: : portionClass 1: 7 %
: Carcinogenic substances: Not applicable
: mutagenic: Not applicable
: Toxic to reproduction: Not applicable

Volatile organic compounds (VOC) content : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Update: Not applicable

according to Detergents Regulation EC 648/2004 : <5% non-ionic surfactants

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

15.2 Chemical Safety Assessment

SECTION 16: Other information

Full text of H-Statements

H290	:	May be corrosive to metals.
H302	:	Harmful if swallowed.
H312	:	Harmful in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H318	:	Causes serious eye damage.
H335	:	May cause respiratory irritation.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Met. Corr.	:	Corrosive to Metals
Skin Corr.	:	Skin corrosion
STOT SE	:	Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Met. Corr. 1	H290
Skin Corr. 1	H314
Eye Dam. 1	H318

Classification procedure:

Calculation method
Based on product data or assessment
Based on product data or assessment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



SANET EXTREME F

WM 0716988

Order number: 0716988

Version 2.2

Revision Date 16.07.2026

Print Date 16.07.2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG_EU / EN

500000006441